












# iRZ MC52iT

**MC52iT** is a dual-band (900/1800 MHz) GSM modem intended for data transmission via cellular communication networks with GPRS support (class 10) and TCP/IP protocol stack. External interfaces: RS232 serial port, TJ-4P4C connector for audio handset connecting, TJ6-6P6C power connector. The main functions include: data transmission by use of CSD and GPRS technologies, reception and transmission of voice signals, faxes and SMS-messages. The modem is controlled by standard AT-commands. MC52iT is designed to operate in automatic data collecting systems of heat and electricity supply meters, vending sale systems, in automatic payment machines, as well as in other systems with wireless data transmission.

	DUAL-BAND		GSM		GPRS CLASS 10
	TCP/IP CONNECTIVITY		INDUSTRIAL INTERFACES		WATCHDOG TIMER
	FAX FUNCTIONALITY		SIM ACCESS PROFILE		EXTENDED TEMPERATURE RANGE



### Frequency bands:

- 900/1800 MHz
- GPRS class 10
- TCP/IP stack

### Features:

- Available network protocols: TCP, UDP, HTTP, FTP, SMTP, POP3
- Control by AT-commands (Hayes 3GPP TS 27.007, TS 27.005)
- Toolkit for SIM-applications
- Timer restart function is realized

### Specification:

- GPRS class 10 – up to 85.6 kbps
- MS class B
- SMS: MT, MO, CB, Text and PDU modes
- CSD up to 14.4 kbps
- USSD
- Fax group 3: class 1

### Voice communication:

- HR/FR/EFR/AMR speech coding
- Hands-free base operations
- Noise reduction function, echo suppression

### Connectors and interfaces:

- DB9 connector for data cable connection (RS232 interface)
- TJ-4P4C connector for audio interface connection
- TJ6-6P6C connector for power supply connection
- FME connector for GSM antenna connection

### Electrical characteristics:

Supply voltage range: 9 V ... 30 V

Supply current not more than:

- At 12 V supply voltage - 200 mA
- At 24 V supply voltage - 100 mA

### Physical parameters:

- Plastic housing
- Dimension not more than: 69 x 75 x 26 mm
- Weight not more than: 100 g
- Operating temperature range: -40°C to +65°C

